



# PROBLOCK PRIMER®

## AEROSOL PRIMER

Product Number: 1411669

PRODUCT DESCRIPTION	APPLICATION CONT.	CAUTIONS
ProBlock Primer® is an oil-based primer that blocks out most stains including water, smoke, ink, pencil and grease. ProBlock Primer® can be used on most interior and exterior (spot-prime only) surfaces and can be topcoated with any latex or oil-based paint.	After priming stained areas, allow to dry 1 hour, test a small area for bleeding by applying the topcoat before painting the entire project. If the stain bleeds through, apply a second coat of primer and retest before top-coating.	<b>CONTAINS CRYSTALLINE SILICA, KETONES, TOLUENE AND XYLENE. DANGER!</b> EXTREMELY FLAMMABLE. Keep away from heat, sparks and open flame. Vapors will accumulate readily and may ignite explosively. Keep area ventilated during use and until all vapors are gone. DO NOT SMOKE - Extinguish all flames, pilot lights and heaters - Turn off stoves, electric tools and appliances, and any other sources of ignition. <b>CONTENTS UNDER PRESSURE.</b> Avoid prolonged exposure to sunlight or heat from radiators, stoves, hot water and other heat sources that may cause bursting. Do not puncture, incinerate, burn or store above 120°F. Keep upright in a cool, dry place. Do not discard empty can in trash compactor. <b>VAPOR HARMFUL.</b> Use with adequate ventilation. Avoid continuous breathing of vapor and spray mist. To avoid breathing vapors or spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, increase fresh air or wear respiratory protection (NIOSH approved) or leave the area. Avoid contact with eyes and skin. Wash hands after using. <b>FIRST AID:</b> In case of eye contact, flush thoroughly with large amounts of water for 15 minutes and get medical attention. For skin contact, wash thoroughly with soap and water. In case of respiratory difficulty, provide fresh air and call physician. <b>DELAYED EFFECTS FROM LONG TERM OVEREXPOSURE.</b> Contains solvents which can cause permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. <b>WARNING:</b> This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. <b>DO NOT TAKE INTERNALLY. KEEP OUT OF THE REACH OF CHILDREN.</b>
SURFACE PREPARATION	CHARACTERISTICS	
<b>WARNING!</b> If you scrape, sand or remove old paint, you may release lead dust. <b>LEAD IS TOXIC.</b> Contact the National Lead Information Hotline at 1-800-424-LEAD or log onto <a href="http://www.epa.gov/lead">www.epa.gov/lead</a> . Remove all surface contamination by washing with an appropriate cleaner, rinse and allow to dry. Existing peeled or checked paint should be scraped and sanded to a sound surface. Glossy surfaces should be sanded dull.	<b>Color:</b> White <b>Coverage:</b> 25 Square Feet <b>Drying Time, @ 77°F, 50% RH:</b> <i>Drying time and recoat times are temperature, humidity, and film thickness dependent.</i> <b>Touch:</b> 20 minutes <b>To Handle:</b> 1 hour <b>Recoat:</b> Anytime <b>Vehicle Type:</b> Alkyd <b>Finish:</b> Flat <b>VOC:</b> Less than 50% <b>Volume Solids:</b> 10 - 25% <b>Weight Solids:</b> 35 - 45% <b>Flash Point:</b> -20°F <b>Gloss (60° Gloss Reading):</b> 0 to 10	
APPLICATION		<b>PERFORMANCE TESTING</b>
Use in a well-ventilated area at temperature range of 0°F to 90°F. Protect adjacent areas from potential overspray with drop cloths. Wear plastic goggles to protect eyes. Shake can for 2 minutes after ball within begins to rattle. Hold can at top and swing bottom of can in a circle. Repeat 10 seconds after each minute of use. Spray 8" to 12" from surface in a sweeping motion. Move can with short dusting strokes releasing button at the end of each stroke. Avoid runs and drips by applying several coats at one spraying. After each use, clear valve by holding can upside down and spraying until only clear gas comes out.		Technical data furnished herein is accurate and true to the best of our knowledge. However, no guarantee of accuracy is expressed or implied. We assume no responsibility or liability as a result of purchase, coverage, application or injuries resulting in misuse.