


**SHERWIN  
WILLIAMS.**

As of 02/14/2012, Complies with:

VOCs Canada	Yes
CAGBC Cl V1.0	Yes
CAGBC NC 09	Yes
MPI # Gloss	114, 154
MPI# Semi-Gloss	141, 147, 153

# ALL SURFACE ENAMEL HP

## 100% Acrylic Interior/Exterior

A42 Series	Gloss
A41 Series	Semi-Gloss
A43 Series	Eg-Shel

### CHARACTERISTICS

All Surface Enamel HP is designed for use on a variety of interior and exterior substrates including wood, metal, drywall and masonry. This high quality coating provides excellent resistance to weather and sunlight, maintaining its gloss and color. The exceptional durability also allows it to be used on doors, windows, baseboards, trim and other high traffic areas.

Color: Many Colors

Coverage: 350 - 400 sq ft/gal  
@ 4.0 mils wet; 1.4 mils dry

Drying Time, @ 25°C (77°F), 50% RH:  
temperature and humidity dependent

Touch: 30 minutes

Recoat: 5 hours

Flash Point: N/A

Finish: Gloss, Semi-Gloss, Eg-Shel

Tinting with CCE:

Base	oz/gal	Strength
Extra White	0-4	100%
Deep Base	8-12	100%
Ultradeep Base	8-12	100%

Vehicle Type: Acrylic

**A41WQ8051 (Semi-Gloss)**

VOC (less exempt solvents):

<50 g/L; 0.42 lb/gal

As per 40 CFR 59.406 and SOR/2009-264, s. 12

Volume Solids: 36 ± 2%

Weight Solids: 45 ± 2%

Weight per Gallon: 9.5 lb/gal ±2%

### SPECIFICATIONS

#### **Aluminum**

2 cts. All Surface Enamel HP Acrylic

#### **Drywall, interior**

1 ct. Premium Wall & Wood Primer

2 cts. All Surface Enamel HP Acrylic

#### **Galvanized Steel**

2 cts. All Surface Enamel HP Acrylic

#### **Masonry, Concrete, Cement, Block**

1 ct. PrepRite Block Filler (optional)

or Loxon Masonry Primer

2 cts. All Surface Enamel HP Acrylic

#### **Steel**

2 cts. All Surface Enamel HP Acrylic

#### **Wood, interior**

1 ct. Premium Wall & Wood Primer

2 cts. All Surface Enamel HP Acrylic

#### **Wood, exterior**

1 ct. Exterior Latex Wood Primer

2 cts. All Surface Enamel HP Acrylic

### SURFACE PREPARATION

**WARNING!** Removal of old paint by sanding, scraping or other means may generate dust or fumes that contain lead. Exposure to lead dust or fumes may cause brain damage or other adverse health effects, especially in children or pregnant women. Controlling exposure to lead or other hazardous substances requires the use of proper protective equipment, such as a properly fitted respirator (NIOSH approved) and proper containment and cleanup. For more information, call your local health authority.

Remove all surface contamination by washing with an appropriate cleaner, rinse thoroughly and allow to dry. **Do not use hydrocarbon solvents for cleaning.** Existing peeled or checked paint should be scraped and sanded to a sound surface. Glossy surfaces should be sanded dull. Stains from water, smoke, ink, pencil, grease, etc. should be sealed with the appropriate primer/sealer.

#### **Aluminum and Galvanized Steel**

Wash to remove any oil, grease, or other surface contamination using a water-based cleaner-degreaser. **Do not use hydrocarbon solvents for cleaning.** Remove all corrosion with sandpaper, steel wool, or other abrading method.

#### **Drywall**

Fill cracks and holes with patching paste/spackle and sand smooth. Joint compounds must be cured and sanded smooth. Remove all sanding dust.



# ALL SURFACE ENAMEL HP

100% Acrylic Interior/Exterior

A42 Series	Gloss
A41 Series	Semi-Gloss
A43 Series	Eg-Shel

## SURFACE PREPARATION

### **Masonry, Concrete, Cement, Block**

All new surfaces must be cured according to the supplier's recommendations—usually about 30 days. Remove all form release and curing agents. Rough surfaces can be filled to provide a smooth surface. If painting cannot wait 30 days, allow the surface to cure 7 days and prime the surface with Loxon Masonry Primer.

### **Steel**

Rust and mill scale must be removed using sandpaper, steel wool, or other abrading method. Bare steel must be primed the same day as cleaned.

### **Wood**

Sand any exposed wood to a fresh surface. Patch all holes and imperfections with a wood filler or putty and sand smooth.

### **Mildew**

Remove before painting by washing with a solution of 1 part liquid bleach and 3 parts water. Apply the solution and scrub the mildewed area. Allow the solution to remain on the surface for 10 minutes. Rinse thoroughly with water and allow the surface to dry before painting. Wear protective eyewear, waterproof gloves, and protective clothing. Quickly wash off any of the mixture that comes in contact with your skin. Do not add detergents or ammonia to the bleach/water solution.

### **Caulking**

Exterior gaps between windows, doors, trim, and other through-wall openings; and interior gaps between walls, ceilings, crown moldings, and other trim can be filled with the appropriate caulk after priming the surface.

## APPLICATION

Apply at temperatures above 10°C, (50°F).

No reduction necessary.

### **Brush**

Use a nylon/polyester brush

### **Roller**

Use a 3/8" woven cover

### **Spray—Airless**

Pressure ..... 1500 psi

Tip ..... .017" - .021"

## CLEANUP INFORMATION

Clean spills, spatters, hands and tools immediately after use with soap and warm water. After cleaning, flush spray equipment with mineral spirits to prevent rusting of the equipment. Follow manufacturer's safety recommendations when using mineral spirits.

## CAUTIONS

Protect from freezing.

Not for use on roofs, floors, or decks.

Do not use colorants formulated for interior use only on exterior surfaces.

### **LABEL CAUTIONS**

Use only with adequate ventilation. To avoid overexposure, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches, or dizziness, increase fresh air, or wear respiratory protection (NIOSH approved) or leave the area. Avoid contact with eyes and skin. Wash hands after using. Keep container closed when not in use. Do not transfer contents to other containers for storage. **FIRST AID:** In case of eye contact, flush thoroughly with large amounts of water. Get medical attention if irritation persists. If swallowed, call Poison Control Center, hospital emergency room, or physician immediately. **DO NOT TAKE INTERNALLY. KEEP OUT OF THE REACH OF CHILDREN.**

HOTW 03/25/2011 A41WQ8051 08 00

The information and recommendations set forth in this Product Data Sheet are based upon tests conducted by or on behalf of The Sherwin-Williams Company. Such information and recommendations set forth herein are subject to change and pertain to the product offered at the time of publication. Consult your Sherwin-Williams representative to obtain the most recent Product Data Sheet.